



CLEAN OIL
BRIGHT IDEAS

Desorber D30

Water Separation from Oil - Max. 2.0 L/hour

Applications: Paper Mills, Steel Mills, Can Industry, Hydraulics, Waste Oil

CJC™ Product Sheet

THE APPLICATION

CJC™ Desorber D30 is used for **separation of water from oils in**

- Paper Mills
- Steel Mills
- Can Industry
- Hydraulic Applications
- Waste Oil Applications
- Bio-diesel
- Etc.

The advantage of the CJC™ Desorbers are that the water separation ability is unaffected by viscosity and additive package. The Desorber treats mineral oils as well as synthetic fluids, and is even able to break stable emulsions. The Desorber D30 is able to remove 2 L/h of water, and is able to maintain the water content within systems to very low levels.

Intended for:

- Oil volumes less than 5000 L
- Viscosity range ISO VG 32-320

THE FUNCTION

The desorption process is based on the principle that heated air can effectively hold large quantities of water. In the Desorber the oil, preheated to 70°C, is met by a counter flow of cold, dry air. The air is heated very quickly by the hot oil and will absorb any water present until the air is saturated.

Water in oil leads to change in viscosity, reduced filter ability, reduced lubricity, formation of rust, bacterial growth and increased degradation of the oil - all factors that lead to reduced lifetime of both system components and the oil.

FEATURES

- Removes water even from emulsified oil
- Extends the lifetime of both oil and components
- Prevents uncontrolled shut downs and reduces maintenance costs
- Easy to connect and operate
- Available as a stationary or mobile unit
- Compact in size



The CJC™ Desorber D30

	Dimensions CJC™ Desorber D30
Height	1,550 mm
Length	950 mm
Width	680 mm
Weight	265 kg
Water removal, max.	2.0 L / hour
Voltage	3 x 400 V
Frequency	50 Hz
Current	13.5 A
Flow inlet (nominal flow)	120 L / hour
Flow outlet (nominal flow)	150 L / hour




CLEAN OIL
BRIGHT IDEAS

Desorber D30


Water Separation from Oil - Max. 2.0 L/hour

Applications: Paper Mills, Steel Mills, Can Industry, Hydraulics, Waste Oil

CJC™ Product Sheet



This document has been prepared by C.C. Jensen A/S of Svendborg, Denmark, and remains the property of the company. Reproduction or use of this document without the consent of C.C.Jensen A/S or its subsidiaries is prohibited. All rights reserved.

Scale:	.	 C.C.JENSEN A/S LØVHOLMEN 13, DK-5700 SVENDBORG, DENMARK FAX NO +45 62 22 46 15 PHONE +45 63 21 20 14	Sign	Date
Customer:	.		Constr.	TIK 06.03.15
Project:	.		Drawn	ADR 06.03.15
Ref.:	.		Appr.	
.	.		Rev. 1	ADR 06.06.15
.	.	Drawing no.	74 004 29-8	
CJC Desorber Type D30 PV-C2DE2/C2DE2M Piping Diagram				