



Product Sheet

APPLICATION

CJC® Filter Insert BNK 15/25 used in CJC® Oil Filters is ideal for filtration of insulating oils in tap changers and refrigerator compressor lube oil.

The BNK Insert is **specially dried** for optimal water and dirt holding capacity. The insert is packed in a water-proof and air-tight barrier foil pouch and **must be fitted instantly** after breaking of the foil. The insert is mounted with a **strainer** in the centre hole (30 µm filtration).

FILTRATION CAPABILITY

• Particle Removal

All CJC® Filter Inserts have the following **filtration degree**:

- **3 µm absolute:**
98.7% of all solid particles > 3 µm
- **0.8 µm nominal:**
50% of all solid particles > 0.8 µm

are retained in each pass.

The **dirt holding capacity** of an BNK 15/25 Insert is **2 litres** of evenly distributed solids.

• Degradation Products

Oxidation by-products, resin / sludge, and varnish are retained by the cellulose material. The cellulose will retain **appr. 1 kg** of degradation products.

• Water Removal

The water absorption potential is up to 55% (i.e. **750 mL H₂O**) of the total contaminant holding capacity.

DIMENSIONS

The figures below are nominal:

Diameter:	15 cm
Height:	25 cm

COMPONENT

CJC® Filter Inserts type BNK consist of bonded discs. Ingredients: Wood cellulose and cotton lint-ers.

IDENTIFICATION

To order the BNK 15/25 Filter Insert, please use:

Article No: PA5601338

