



# Blue Baleen OilAbsorb Inserts (OAI)

Polishing Bilge Water to below 5 ppm

## Product Sheet

### APPLICATION

The **CJC® Blue Baleen OilAbsorb Inserts OAI** are used in our **CJC® Blue Baleen OilAbsorb Series**, for fine polishing of bilge water.

After polishing to below 5 ppm, the cleanliness of the water exceeds the requirements in most environmental regulations.

### ABSORPTION CAPABILITY

All **CJC® OilAbsorb Inserts OAI** have an **oil holding capacity of 5-6 kg** (per 2 inserts).

The combination of structure and material makes the insert extremely effective in absorbing to a **polishing degree of 1-5 ppm**.

### DIMENSIONS

The figures below are nominal (per insert):

Diameter:	38 cm
Height:	25 cm
Weight	4,7 kg

### COMPONENT

The **CJC® OilAbsorb Insert OAI** consist of multi-layered polypropylene.

### IDENTIFICATION

To order the **OilAbsorb Insert OAI**, please use:

**Article No:** PA5609418  
(OAI 2x38/25)



*CJC® Blue Baleen OilAbsorb Inserts OAI 2x38/25*

### TECHNICAL DATA

Model		OA 38/50	OA 38/100	2x OA 38/100
OilAbsorb Insert OAI 2x38/25	qty	1	2	4
Oil holding capacity	kg/lb	5-6/11-13	10-12/22-26	20-24/44-53
Temperature, max.	°C/°F	105/221		
Flow, max.	ltr/hour	1,250	2,500	5,000

### PATENT

Patented technology for **CJC® Blue Baleen OilAbsorb Insert**; EP2165977A1