



Desorber D88

Water Removal from Oil - Max. 15 L/hour
Applications e.g.: Steel Mills, Paper Mills, Waste Oil

Product Sheet

THE APPLICATION

CJC® Desorber D88 is used for removal of water from oils in

- Steel Mills
- Paper Mills
- Waste Oil Recovery Plants
- Biodiesel Plants
- Large Hydraulic Systems

The advantage of the CJC® Desorbers is that the water removal ability is unaffected by viscosity and additive package. The Desorber treats mineral oils as well as synthetic fluids, and is even able to break stable emulsions.

The CJC® Desorber D88 is able to remove up to 15 L/h of water, and can dry the oil down to a water content of < 100 ppm, depending on the oil type.

Intended for:

- Oil volumes less than 50,000 L
- Viscosity range ISO VG 32-1000

THE FUNCTION

The desorption process is based on the principle that heated air can effectively hold large quantities of water. In the Desorber the oil, preheated to 60-85 °C, is met by a counter flow of cold, dry air. The air is heated very quickly by the hot oil and will absorb any water present until the air is saturated.

Water in oil leads to change in viscosity, reduced filter ability, reduced lubricity, formation of rust, bacterial growth and increased degradation of the oil - all factors that lead to reduced lifetime of both system components and the oil.

FEATURES

- Removes water even from emulsified oil
- Extends the lifetime of both oil and components
- Prevents uncontrolled shut downs and reduces maintenance costs
- Easy to connect and operate



The CJC® Desorber 88

TECHNICAL DATA

Voltage	V	3 x 400
Frequency	Hz	50
Power consump.	kW	60
Current	A	86
Flow inlet	L/h gal/h	1400 370
Viscosity Range		ISO VG 32-1000
Ambient operation temperature	°C °F	0-40 32-104
Dimensions, WxDxH	mm in	2000 x 1600 x 2500 78.7 x 63 x 98.4
Weight	kg lb	1750 3858
System pressure	bar psi	0.5 bar inlet pressure, max
Article no.		FA7400223



Desorber D88

Water Removal from Oil - Max. 15 L/hour
Applications e.g.: Steel Mills, Paper Mills, Waste Oil

Product Sheet

